

Phone
Fax

TOP-S 80/10 3~ PN 6
System: Standard pump

WILO

Customer

Project

Customer no.

Project no.

Contact

Position no.


Care of

Location

Date

2013-12-04

Page 1 / 1



Requested data

Flow	0	m ³ /h
Head	0	m
Fluid	Water, pure	
Fluid temperature	20	°C
Density	0.9983	kg/dm ³
Kinematic viscosity	1.005	mm ² /s
Vapor pressure	0.02337	bar

Pump data

Make	WILO
Type	TOP-S 80/10 3~ PN 6
Pumpe type	Single head pump
Pressure rating	PN6
Min. fluid temperature	-20 °C
Max. fluid temperature	130 °C

Hydraulic data (duty point)

Flow	m ³ /h
Head	m
Power input P1	kW
Speed	2800 1/min

Minimum suction head

Temperature	50	95	110	130	°C
Minimum suction head	3	10	16	29	m

Materials / Shaft seal

Housing	Cast iron
Shaft	X 46 Cr 13
Impeller	Fiber-reinforced PP
Bearing	Metal impregnated carbon

Dimensions per pump

mm							
a1	258	b3	159	l2	119	dL	19
a2	95	b4	66	n	4	Pg	2 x 13,5
a3	130	b5	66	k	150		
b1	135	l0	360	d	132		
b2	108	l1	180	D	200		

Suction side	DN 80	/ PN 6
Discharge side	DN 80	/ PN 6
Weight	28	kg

Motordata per Motor/Pump/

Energy efficiency class	C
Rated power P2	1.1 kW
Power input P1	1.68 kW
Nominal speed	2800 1/min
Rated voltage	3~400 V, 50 Hz
Max. current	3.13 A
Degree of protection	IP X4D
Permitted voltage tolerance	+/- 10%

Item no. of standard version 2080065

